


· Supplier : JSMICRO electro-mechanics
 · Product : Multi-layer Ceramic Capacitor

· JSMICRO P/N : **CL03A105MQ3CSNH**
 · Description : **CAP, 1uF, 6.3V, ±20%, X5R, 0201**

A. JSMICRO Part Number

CL
①
03
②
A
③
105
④
M
⑤
Q
⑥
3
⑦
C
⑧
S
⑨
N
⑩
H
⑪

① Series	JSMICRO Multi-layer Ceramic Capacitor		
② Size	0201 (inch code)	L: 0.60 ± 0.05 mm	W: 0.30 ± 0.05 mm
③ Dielectric	X5R	⑧ Inner electrode Termination	Ni
④ Capacitance	1 uF	⑨ Plating	Control code
⑤ Capacitance tolerance	±20 %	⑩ Product	Sn 100% (Pb Free)
⑥ Rated Voltage	6.3 V	⑪ Special	Size control code
⑦ Thickness	0.30 ± 0.05 mm		Reserved for future use
			Cardboard Type, 7" reel

B. Structure & Dimension


JSMICRO P/N	Dimension(mm)			
	L	W	T	BW
CL03A105MQ3CSNH	0.60 ± 0.05	0.30 ± 0.05	0.30 ± 0.05	0.15 ± 0.05

C. JSMICRO Reliability Test and Judgement Condition

	Judgement	Test condition
Capacitance	Within specified tolerance	1 kHz $\pm 10\%$ / $0.5 \pm 0.1 V_{rms}$
Tan δ (DF)	0.125 max.	*A capacitor prior to measuring the capacitance is heat treated at $150^\circ C \pm 0/-10^\circ C$ for 1 hour and maintained in ambient air for 24 ± 2 hours.
Insulation Resistance	10,000 Mohm or $10 \text{ Mohm} \times \mu F$ Whichever is smaller	Rated Voltage 60~120 sec.
Appearance	No abnormal exterior appearance	Microscope ($\times 10$)
Withstanding Voltage	No dielectric breakdown or mechanical breakdown	250% of the rated voltage
Temperature Characteristics	X5R From $-55^\circ C$ to $85^\circ C$, Capacitance change should be within $\pm 15\%$	
Adhesive Strength of Termination	No peeling shall be occur on the terminal electrode	200g-f, for 10 ± 1 sec.
Bending Strength	Capacitance change : within $\pm 12.5\%$	Bending to the limit (1mm) with 1.0mm/sec.
Solderability	More than 75% of terminal surfaces to be soldered newly	SnAg3.0Cu0.5 solder $245 \pm 5^\circ C$, 3 ± 0.3 sec. (preheating : $80 \sim 120^\circ C$ for $10 \sim 30$ sec.)
Resistance to Soldering Heat	Capacitance change : within $\pm 7.5\%$ Tan δ , IR : initial spec.	Solder pot : $270 \pm 5^\circ C$, 10 ± 1 sec.
Vibration Test	Capacitance change : within $\pm 5\%$ Tan δ , IR : initial spec.	Amplitude : 1.5mm From 10Hz to 55Hz (return : 1min.) 2hours \times 3 direction (x, y, z)
Moisture Resistance	Capacitance change : within $\pm 12.5\%$ Tan δ : 0.25 max IR : 500 Mohm or $1 \text{ Mohm} \times \mu F$ Whichever is smaller	With rated voltage $40 \pm 2^\circ C$, 90~95%RH, $500 \pm 12/-0$ hrs
High Temperature Resistance	Capacitance change : within $\pm 12.5\%$ Tan δ : 0.25 max IR : 1,000 Mohm or $2 \text{ Mohm} \times \mu F$ Whichever is smaller	With 150% of the rated voltage Max. operating temperature $1,000 \pm 48/-0$ hrs
Temperature Cycling	Capacitance change : within $\pm 15\%$ Tan δ , IR : initial spec.	1 cycle condition Min. operating temperature $\rightarrow 25^\circ C$ \rightarrow Max. operating temperature $\rightarrow 25^\circ C$ 5 cycle test

※ The reliability test condition can be replaced by the corresponding accelerated test condition.

D. Recommended Soldering method :

Reflow (Reflow Peak Temperature : $260 \pm 5^\circ C$, 30sec.)

 Product specifications included in the specifications are effective as of March 1, 2013.
 Please be advised that they are standard product specifications for reference only.
 We may change, modify or discontinue the product specifications without notice at any time.
 So, you need to approve the product specifications before placing an order.
 Should you have any question regarding the product specifications,
 please contact our sales personnel or application engineers.