

Customer Reviews	—
Price	—
Test Connectors	Twisted-pair: UTP, FTP, SSTP 8-pin modular jack accepts 8-pin modular (RJ45) and 4-pin modular (RJ11) plugs; Coax: F-connector for 75 Ω , 50 Ω , 93 Ω cables.
Cable Tests	Length (460 m or 1500 ft. with resolution to 0.3 m or 1 ft.), wiremap to TIA-568A/B standards, remote ID locators; displays results on one screen.
Tone Generator	IntelliTone digital tone: [500 KHz]; analog tones: [400Hz, 1KHz]
PoE Detection	Solicits and detects the presence of 802.3af compatible PoE (Power over Ethernet) devices.
Ethernet Port Test	Advertised speed of 802.3 Ethernet ports (10/100/1000)
Power Source	Battery type: 2 AA (NEDA 15A, IEC LR6) alkaline batteries. Battery life: 20 hours of typical use. Other compatible battery types: 2 AA photo lithium, NIMH, NICAD
Dimensions	3 in x 6.4" x 1.4 in (7.6 cm x 16.3 cm x 3.6 cm)
Weight	0.8 lbs. (363 grams)
Display	Monochrome liquid crystal display (LCD) with backlight
Calibration	User-configurable NVP for twisted pair and coax, determines actual NVP with known len

Price	—
Operating Temperature	32 °F to 113 °F (0 oC to 45 oC)
Storage Temperature	-4 °F to +140 °F (-20 oC to +60 oC)
Operating Humidity	90 % (50 °F to 95 °F; 10 oC to 35 oC)
(%RH without condensing)	75 % (95 °F to 113 °F; 35 oC to 45 oC)
Shock Vibration	Meets requirements for MIL-PRF-28800F for Class 2 random vibration, 1 m drop test with and without wiremap adapter attached.
Safety	EN 61010-1 2nd Edition
Altitude	4000 m, Storage: 12000 m
EMC	EN 61326-1
Agency Certifications	N10140 C-Tick EMC standard, FCC Part 15 Class A, CE European Union Directives
Warranty	One year